

Medium Temp. Air Cooling Refrigerated Air Dryer

Brand: Apureda Air Dryer

Product Code: Refrigerated Air Dryer

Availability: In Stock

Weight: 0.00kg

Dimensions: 0.00cm x 0.00cm x 0.00cm

Call for Price:

Short Description

[Medium Temp. Air Cooling Refrigerated Air Dryer](#)

Description

Since 2000, Apureda has been delivering quality, industry leading compressed air dryers and accessories for production lines and facilities all over the world. Our precise engineering and designs provide reliable products that will protect your operations for years to come.

Our knowledge and advanced compressed air dryer technology in the field of compressed air, gas, and fluid separation, extends from the compressor room to all points of use in the factory.



Working Condition & Parameters

Air inlet temp.: 2~45°C

Pressure dew point: 10°C

Pressure loss: ≤5%P

Ambient temp.: 2~40°C

Air inlet pressure: 0.4~1.0MPa

Cooling: Air cooled

Standard working condition?

Air inlet temp.: 38°C

Air inlet pressure: 0.7MPa(G)

SPECIFICATION



Model	Flow rate	Refrigeration	Blower	Power supply	Dimension mm			Connection Port	Weight
					L	W	H		
	(m ³ /min)	Power (W)	power (W)					? kg ?	
CFKA-15N	2	0.63	100	220V 50Hz	700	420	655	Rp1	62
CFKA-30N	4	0.94	135		800	470	705	Rp1-1/2	85
CFKA-40N	5.5	1.05	135		800	470	855	Rp1-1/2	100
CFKA-50N	7	1.13	190		880	520	855	Rp1-1/2	115
CFKA-60N	8.5	1.49	190		970	520	875	Rp1-1/2	130
CFKA-75N	11	1.74	250		1050	640	1065	Rp2	185
CFKA-90N	13	1.97	270		1200	640	1065	Rp2	190
CFKA-100N	15	2.2	270		1200	640	1065	Rp2	195
CFKA-125N	18	3.14	380	380V 50Hz	1200	640	1215	DN65	250
CFKA-150N	23	3.8	380		1350	640	1215	DN65	290
CFKA-175N	28	5.5	380		1450	790	1415	DN80	380
CFKA-200N	33	5.8	380		1550	790	1415	DN80	460
CFKA-250N	38	7.5	460		1650	840	1515	DN100	520
CFKA-300N	45	8.2	460		1800	840	1515	DN100	720
CFKA-400N	55	8.82	840		2100	975	1345	DN100	820
CFKA-500N	65	11.03	1260		2400	1200	1520	DN100	1080
CFKA-75	75	11.25	1260	2500	1200	1520	DN12	1150	

-600N							5	
CFKA -700N	85	14.7	1650	2700	1200	1680	DN12 5	1500
CFKA -800N	110	18.37	2200	2900	1300	1750	DN15 0	2200
CFKA -900N	130	22.05	2200	3200	1300	1750	DN15 0	2350
CFKA -1000 N	160	28.8	2400	3200	1600	2200	DN20 0	2455
CFKA -1200 N	190	33.08	3200	3200	1600	2300	DN20 0	2720
CFKA -1500 N	220	36.75	3400	3300	1600	2400	DN20 0	3120

Standard of screw is in accordance with GB/T7306

Standard of flange is in accordance with HG20592

Any change of model, specification and color shall not be advised additionally, subject to the real products.

Please refer to the corresponding brochure if you order other models.