

# High Temp. Air Cooling Refrigerated Air Dryer

**Brand:** Apureda Air Dryer  
**Product Code:** Refrigerated Air Dryer  
**Availability:** In Stock  
**Weight:** 0.00kg  
**Dimensions:** 0.00cm x 0.00cm x 0.00cm  
**Call for Price:**

## Short Description

### [High Temp. Air Cooling Refrigerated Air Dryer](#)

## Description

Since 2000, Apureda has been delivering quality, industry leading compressed air dryers and accessories for production lines and facilities all over the world. Our precise engineering and designs provide reliable products that will protect your operations for years to come.

Our knowledge and advanced compressed air dryer technology in the field of compressed air, gas, and fluid separation, extends from the compressor room to all points of use in the factory.



## Working Condition & Parameters

Air inlet temp.: 28°C

Pressure dew point: 10°C

Pressure drop: 5%P

Ambient temp.: 38°C

Air inlet pressure: 0.4~1.0MPa

Cooling: Air cooled

Standard working condition?

Air inlet temp.: 65°C

Air inlet pressure: 0.7MPa(G)

## SPECIFICATION

Model	Flow rate (m <sup>3</sup> /min)	Refrigeration Power(W)	Blower power(W)	Power supply	Dimension mm			Connection Port	Weight (kg)
					L	W	H		
CFKA-15NH	2	0.63	125	220V 50HZ	750	470	715	R1	83
CFKA-30NH	4	0.94	250		800	500	960	R1-1/2	105
CFKA-40NH	5.5	1.05	250		850	500	960	R1-1/2	115
CFKA-50NH	7	1.13	270		900	540	1065	R1-1/2	135
CFKA-60NH	8.5	1.49	270		970	540	1115	R1-1/2	150
CFKA-	11	1.74	500		1100	690	1190	R2	195

75NH									
CFKA-90NH	13	1.97	540		1250	690	1190	R2	205
CFKA-100NH	15	2.2	540		1250	690	1190	R2	215
CFKA-125NH	18	3.14	540	380V 50HZ	1350	740	1315	DN65	305
CFKA-150NH	23	3.8	760		1450	740	1315	DN65	385
CFKA-175NH	28	5.5	760		1550	890	1515	DN80	445
CFKA-200NH	33	5.8	760		1650	890	1515	DN80	525
CFKA-250NH	38	7.5	920		1750	940	1665	DN100	650
CFKA-300NH	45	8.2	920		1800	940	1665	DN100	780
CFKA-400NH	55	8.82	1410		2100	975	1725	DN100	920
CFKA-500NH	65	11.03	1950		2400	1200	1950	DN100	1230
CFKA-600NH	75	11.25	2445		2500	1200	1965	DN125	1350
CFKA-700NH	85	14.7	2910		2700	1200	2085	DN125	1700
CFKA-800NH	110	18.37	3460		2900	1300	2265	DN150	2300
CFKA-900NH	130	22.05	3850		3200	1300	2265	DN150	2470
CFKA-1000NH	160	28.8	4800		3200	1600	2300	DN200	2595
CFKA-1200NH	190	33.08	6400		3200	1600	2400	DN200	2890
CFKA-1500NH	220	36.75	6800		3300	1600	2500	DN200	3290

Standard of screw is in accordance with GB/T7306

Standard of flange is in accordance with HG20592

Any change of model, specification and color shall not be advised additionally, subject to the real products.

Please refer to the corresponding brochure if you order other models.